

Cisco Unified IP Phone 9951

Product Overview

The Cisco Unified IP Phone 9951 is an executive class collaboration endpoint that provides voice, video, applications and accessories. Highlights include Gigabit Ethernet, Wideband Audio, Color Display along with a new industrial design and user interface designed for simplicity and high usability. Accessories, sold separately, include a standard definition USB camera, Jawbone ICON for Cisco Bluetooth headset, color Key Expansion Module plus support for Bluetooth, USB devices. Application support includes XML capabilities.

Features and Benefits

- Newly developed industrial design and user experience designed for use with its VGA display
- H.264 video support for 2-way standard definition calling with USB support for the Cisco Unified IP Camera
- Gigabit Ethernet network connectivity and switch port available for a downstream PC
- Embedded Bluetooth radio and 2 USB ports for headsets and the camera
- Firmware support for XML applications

Table 1. Features and Benefits

Feature	Benefits
Hardware	
Ergonomic Design	Highly usable and intuitive arrangement of lines, features and calls. Transfer, Conference and Hold appear on hard keys to reduce the number of presented softkeys to a maximum of 4 per call state.
Customization	This model can be ordered as Arctic White or Charcoal Gray. Handsets are available internationally as slimline (5oz, 140g) or standard (6oz, 170g) and can be mixed and matched between users within the same work environment to enable a feeling of customization and ownership among the users.
Display	VGA presentation for calling, video calling and applications. 5-inch (10 cm) graphical TFT color display, 24-bit color depth, 640 x 480 effective pixel resolution, with backlight. Display also supports localization requiring double-byte Unicode encoding for fonts.
Ethernet	Internal 2-port Cisco Ethernet switch allows for a direct connection to a 10/100/1000 BASE-T Ethernet network through an RJ-45 interface with single LAN connectivity for both the phone and a colocated PC. System administrator can designate separate VLANs (802.1Q) for the PC and phone, providing improved security and reliability of voice and data traffic.
Bluetooth	Mobility for headset users within 30 feet of their desktop to enable the freedom to go to the printer, a colleague's desk or nearby private location while on a call. The 9951 supports the Hands-free and Headset Bluetooth profiles.
USB	2 USB ports accelerate the usability of call handling and applications by enabling accessories such as the Cisco Unified IP Camera, wired and wireless headsets.
External Audio Ports	General Purpose Audio In and Audio Out ports enable a relaxed speakerphone experience over external speakers and microphone.
5 Lines Expanding to 77 with 2 Key Expansion Modules	The convenience of many speed dials or programmable features, or the necessity of following the activity of many lines. Up to 200 calls supported per device.
Buttons	5 feature buttons with state indicating LEDs 5 call session buttons with state indicating LEDs Applications, Directories, Voicemail Conference, Transfer, Hold Volume Up/Down Back-lit Mute, Speakerphone, Headset Back, End Call, 5-Way Navigation Pad Arabic keypad (only available through unique SKUs. See table 5 for more details)

Feature	Benefits
Accessories	
Key Expansion Module	Available separately, enables advanced use of lines, speed dials and features.
Cisco Unified IP Camera	Available separately, enables 2-way video calling between phones or to a media conference unit.
Headset Support	Integrated design & advanced, updateable firmware for Jawbone ICON for Cisco Bluetooth headset which also works with all major mobile phone models. Also supports standard Bluetooth and USB headsets supported via the hands-free and headset Bluetooth profiles. Wideband analog headset support also provided via a dedicated RJ9 headset port on the rear of the phone.
Firmware	
New User Experience	Advanced organization of lines, speed dials and programmable features separate from call appearances. Great for those who make few calls per day, better for those who handle dozens of calls per hour.
SIP Signaling	SIP interoperation with the call control and partner applications enables a rich unified communications solution.
Application Support	XML applications provided by Cisco's application development partners or customers' own development staff.

Unified Communications Manager Support

- Cisco Unified Communications Manager version 7.1(3a)SU1 or later.
 - Some features require more recent version of UC Manager and Dev Pack support. Please check the release notes for more information.
- Survivable Remote Site Telephony (SRST) version 4.3 or later.
- CME 8.6 or later

Licensing

Phone licensing is dependent on the call control platform and its policies. For the Cisco Unified Communications Manager, the 9951 requires 4 Device License Units (DLUs) or an Enhanced IP User Connect License for UCM release 7.1(5) or later. There are no special licence plus phone bundles for Tier II distributors. The 9951 is not support on non-Cisco third party call control systems.

Product Specifications

Table 2. Product Specifications

Protocols	SIP for signaling H.264 for video
Connectivity	10/100/1000 wired Ethernet network port plus switched PC port
Options	Arctic White or Charcoal Gray color Slimline (5oz, 140g) or Standard (6oz, 170g) handset
Language Support	Arabic, Bulgarian, Catalan, Chinese (People's Republic of China), Chinese (Hong Kong), Chinese (Taiwan), Croatian, Czech, Danish, Dutch, English - plus localized prompts for the UK, Estonian, French, Finnish, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Latvian, Lithuanian, Norwegian, Polish, Portuguese (Portugal), Portuguese (Brazil), Romanian, Russian, Spanish (Spain), Slovak, Swedish, Serbian (Republic of Serbia), Serbian (Republic of Montenegro), Slovenian, Thai, Turkish
Physical Dimensions (HxWxD)	9.2" (23.4 cm) x 10.33" (26.25 cm) x 1.56" (3.97 cm) In slab mode with the footstand removed
Power	IEEE Power over Ethernet 802.3af and 802.3at supported, class 4. The 9951 is compatible with both class 3 and class 4 IEEE PoE switch blades and supports both Cisco Discovery Protocol (CDP) and Link Layer Discovery Protocol - Power over Ethernet (LLDP-PoE)
Temperature Range	
Operational Temperature	32 to 104°F (0 ~ 40°C)
Relative Humidity	10 to 95% (noncondensing)
Storage Temperature	14 to 140°F (-10 to 60°C)

Quantity Shipped per Pallate	320 units
-------------------------------------	-----------

SKU	Description	Weight: Hardware lb (kg)	Weight: Single Carton lb (kg)	Weight: Master Pack of 8 Cartons lb (kg)
CP-9951-C-K9=	Cisco Unified IP Endpoint 9951, Charcoal, Standard Handset	3.43(1.558)	4.34(1.970)	36.46(16.540)
CP-9951-CL-K9=	Cisco Unified IP Endpoint 9951, Charcoal, Slimline Handset	3.37(1.527)	4.30(1.951)	36.13(16.389)
CP-9951-W-K9=	Cisco Unified IP Endpoint 9951, Arctic White, Standard Handset	3.57(1.620)	4.57(2.074)	38.29(17.370)
CP-9951-WL-K9=	Cisco Unified IP Endpoint 9951, Arctic White, Slimline Handset	3.50(1.589)	4.50(2.040)	37.70(17.100)
CP-9951-C-A-K9=	Cisco UC Phone 9951, Charcoal, Arabic keypad, Std HS	3.43(1.558)	4.34(1.970)	36.46(16.540)
CP-9951-W-A-K9=	Cisco UC Phone 9951, White, Arabic keypad, Std HS	3.57(1.620)	4.57(2.074)	38.29(17.370)
CP-9951-C-A-C-K9=	Cisco UC Phone 9951, Charcoal, Arabic keypad, Std HS, Camera	-	-	-
CP-9951-W-A-C-K9=	Cisco UC Phone 9951, White, Arabic keypad, Std HS, Camera	-	-	-
CP-89/9900-HS-C=	Spare Handset for 8900 or 9900 Series, Charcoal, Standard	0.39(0.177)	-	-
CP-89/9900-HS-CL=	Spare Handset for 8900 or 9900 Series, Charcoal, Slimline	0.32(0.146)	-	-
CP-89/9900-HS-W=	Spare Handset for 8900 or 9900 Series, Arctic White, Standard	0.41(0.187)	-	-
CP-89/9900-HS-WL=	Spare Handset for 8900 or 9900 Series, Arctic White, Slimline	0.34(0.156)	-	-

Table 3. Calling Features

Feature	Specifications
Calling Feature Support	<ul style="list-style-type: none"> • + Dialing • Abbreviated dialing • Adjustable ringing and volume levels • Adjustable display brightness • Agent Greeting/Whisper Coaching • Application Launch Pad • Auto-answer • Auto-detection of headset • Barge • Callback • Call forward • Call forward notification • Call history lists • Call park • Call pickup • Call timer • Call waiting • Caller ID • Corporate directory • Conference • Direct transfer • Extension mobility service • Fast-dial service • Forced access codes/Client matter codes • Group call pickup • Hold • Intercom • Immediate divert • Join

Feature	Specifications
	<ul style="list-style-type: none"> • Last-number redial • Malicious-caller ID • Message-waiting indicator • Meet-me conference • Music on hold • Mute • Network profiles (automatic) • On- and off-network distinctive ringing • OPickUp • Personal directory • Predialing before sending • Privacy • Redial • Ring tone per line appearance • Service URL • Shared line • Time and date display • Transfer • Visual Voice Mail • Voice Mail
Audio Codec Support	G.711a, G.711u, G.729a, G.729ab, G.722, iSAC and iLBC audio compression codecs.
Configuration Options	<ul style="list-style-type: none"> • Dynamic Host Configuration Protocol (DHCP) client or static configuration • Support for online firmware upgrades using Trivial File Transfer Protocol (TFTP) • Domain Name System (DNS) • HTTP Firmware Management
Network Features	<ul style="list-style-type: none"> • Cisco Discovery Protocol (CDP) • Link Layer Discovery Protocol Power over Ethernet (LLDP-PoE) • Transparent secure roaming • Provisioning of network parameters through DHCP • Switch Auto-Negotiation • VPN Client
Security Features	<ul style="list-style-type: none"> • Certificates • Image authentication • Device authentication • File authentication • Signaling authentication • Media encryption using Secure Real-Time Protocol (SRTP) • Signaling encryption using Transport Layer Security (TLS) Protocol • Certificate authority proxy function (CAPF) • Secure profiles • Encrypted configuration files
Provisioning and Manufacturing	<ul style="list-style-type: none"> • Cisco Unified Communications Manager Express Version Negotiation • Web server for configuration and statistics • QoS reporting: jitter, delay, dropped packets, and latency on a per-call basis • Real Time Control Protocol (RTCP) support and monitoring • Syslog

Table 4. Video Features and Benefits

Feature	Specifications
Video Standards	H.264/AVC
Frame Rates	30 fps (maximum) using H.264/AVC for video
Frame or Picture Formats	SQCIF (128 x 96 pixels) QCIF (176 x 144 pixels)

	QVGA (320 x 240 pixels) SIF (352 x 240 pixels) CIF (352 x 288 pixels) VGA (640 x 480 pixels)
--	---

Ordering Information

Help customers understand all the components or parts they need to purchase in order to install and use the product. This section also provides a direct link to the Cisco Ordering Tool and lists part numbers for customer convenience.

To place an order, visit the [Cisco Ordering Home Page](#). To download software, visit the [Cisco Software Center](#).

Table 5. Ordering Information

Product Name	Part Number
Cisco Unified IP Phone 9951, Charcoal, Standard Handset, Spare	CP-9951-C-K9=
Cisco Unified IP Phone 9951, Charcoal, Slimline Handset, Spare	CP-9951-CL-K9=
Cisco Unified IP Phone 9951, White, Standard Handset, Spare	CP-9951-W-K9=
Cisco Unified IP Phone 9951, White, Slimline Handset, Spare	CP-9951-WL-K9=
Cisco UC Phone 9951, Charcoal, Arabic keypad, Std HS	CP-9951-C-A-K9=
Cisco UC Phone 9951, White, Arabic keypad, Std HS	CP-9951-W-A-K9=
Cisco UC Phone 9951, Charcoal, Arabic keypad, Std HS, Camera	CP-9951-C-A-C-K9=
Cisco UC Phone 9951, White, Arabic keypad, Std HS, Camera	CP-9951-W-A-C-K9=
Cisco Unified IP Phone 9951, Charcoal, Standard Handset Configurable with Camera and Jawbone ICON for Cisco Headset. (Offered in United States only)	CP-9951-CHSUS-K9:
Cisco Unified IP Phone 9951, Charcoal, Slimline Handset Configurable with Camera and Jawbone ICON for Cisco Headset. (Offered in United States only)	CP-9951-CLHSUS-K9:

Table 6. Spare Parts

Spare Handset for 8900 or 9900 Series, White, Slimline	CP-89/9900-HS-WL=
Spare Handset for 8900 or 9900 Series, White, Standard	CP-89/9900-HS-W=
Spare Handset for 8900 or 9900 Series, Charcoal, Slimline	CP-89/9900-HS-CL=
Spare Handset for 8900 or 9900 Series, Charcoal, Standard	CP-89/9900-HS-C=
Spare Handset Cord, White	CP-HS-CORD-W=
Spare Handset Cord, Charcoal	CP-HS-CORD-C=
Spare footstand for 8900 or 9900 Series, White	CP-89/9900-FS-W=
Spare footstand for 8900 or 9900 Series, Charcoal	CP-89/9900-FS-C=

Table 7. Accessories

Accessories include the camera, Jawbone ICON for Cisco Bluetooth headset, Key Expansion Modules and Locking Wall Mount Kits. The Cisco Unified Video Camera is offered at no additional hardware price when ordered with the configurable phone SKUs or with phone and camera bundles listed in Table 5.

For more information about accessories, go to:

- [Cisco Unified Video Camera for the 9900 Series IP Phone](#)
- [Jawbone ICON for Cisco Bluetooth Headset](#)
- [Cisco Unified IP Color Key Expansion Module](#)

Cisco Unified Video Camera for the 9900 Series IP Phone, Charcoal	CP-CAM-C=
Cisco Unified Video Camera for the 9900 Series IP Phone, White	CP-CAM-W=
Jawbone ICON for Cisco Bluetooth Headset, Charcoal, Australia Power Cube, Spare	CP-ICON-HS-C-AU=
Jawbone ICON for Cisco Bluetooth Headset, Arctic White, Australia Power Cube, Spare	CP-ICON-HS-W-AU=
Jawbone ICON for Cisco Bluetooth Headset, Charcoal, Europe Power Cube, Spare	CP-ICON-HS-C-CE=
Jawbone ICON for Cisco Bluetooth Headset, Arctic White, Europe Power Cube, Spare	CP-ICON-HS-W-CE=
Jawbone ICON for Cisco Bluetooth Headset, Charcoal, North America Power Cube, Spare	CP-ICON-HS-C-NA=
Jawbone ICON for Cisco Bluetooth Headset, Arctic White, North America Power Cube, Spare	CP-ICON-HS-W-NA=
Jawbone ICON for Cisco Bluetooth Headset, Charcoal, United Kingdom Cube, Spare	CP-ICON-HS-C-UK=
Jawbone ICON for Cisco Bluetooth Headset, Arctic White, United Kingdom Cube, Spare	CP-ICON-HS-W-UK=
Cisco Unified IP Color Key Expansion Module, Charcoal	CP-CKEM-C=
Cisco Unified IP Color Key Expansion Module, White	CP-CKEM-W=
Locking Wallmount Kit for 8900 or 9900 Series, Charcoal	CP-89/9900-LWMK-C=
Locking Wallmount Kit for 8900 or 9900 Series, Arctic White	CP-89/9900-LWMK-W=
Locking Wallmount Kit for 8900 or 9900 Series and KEM, Charcoal	CP-89/9900-LK-K-C=
Locking Wallmount Kit for 8900 or 9900 Series and KEM, Arctic White	CP-89/9900-LK-K-W=

Table 8. Local Power Options: Cube and Regional Cords

The power cube is new for the 8900 and 9900 Series IP Phones, but the cords are the same cords as used with the 7900 series. Power Cube 4 supports up to 44W and is internationally rated for different power grids worldwide.

Product Name	Part Number
Cisco Unified IP Endpoint Power Cube 4: 48V; 0.917A; 47-63Hz; 100-240V~0.8A	CP-PWR-CUBE-4=
Asia Pacific	CP-PWR-CORD-AP=
Argentina	CP-PWR-CORD-AR=
Australia	CP-PWR-CORD-AU=
European Community	CP-PWR-CORD-CE=
China	CP-PWR-CORD-CN=
Japan	CP-PWR-CORD-JP=
North America	CP-PWR-CORD-NA=
Switzerland	CP-PWR-CORD-SW=
United Kingdom	CP-PWR-CORD-UK=

Cisco Services

Cisco Services integrates closely with CMO teams as an essential element of any technology solution. Please contact your Cisco Services marcom manager if you have not already received targeted services content blocks for integration. Please e-mail ca-marcom@cisco.com if you are not sure of the appropriate contact.

The following text is a **placeholder** and should ideally be replaced with targeted content:

Cisco Services make networks, applications, and the people who use them work better together.

Today, the network is a strategic platform in a world that demands better integration between people, information, and ideas. The network works better when services, together with products, create solutions aligned with business needs and opportunities.

The unique Cisco Lifecycle approach to services defines the requisite activities at each phase of the network lifecycle to help ensure service excellence. With a collaborative delivery methodology that joins the forces of Cisco, our skilled network of partners, and our customers, we achieve the best results.




Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

 Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)