

Cisco Unified Wireless IP Phone 7920 Multi-Charger

The Cisco® Unified Communications system of voice and IP communications products and applications enables organizations to communicate more effectively—helping them to streamline business processes, reach the right resource the first time, and impact the top and bottom line. The Cisco Unified Communications portfolio is a key part of the Cisco Business Communications Solution—an integrated solution for organizations of all sizes which also includes network infrastructure, security, and network management products, wireless connectivity, and a lifecycle services approach, along with flexible deployment and outsourced management options, end-user and partner financing packages, and third-party communications applications.

FEATURES

The Cisco Unified Wireless IP Phone 7920 Multi-Charger (Figure 1) is ideal for environments where customers have multiple shifts and need to keep their Cisco Unified Wireless IP Phone 7920 charged throughout the day. The multi-charger can charge up to 6 phones and 6 batteries simultaneously. Its flexible design allows the unit to be either placed on a desk or mounted on the wall to save desk space. Table 1 gives features of the multi-charger, Table 2 gives its specifications, and Table 3 gives certification and compliance information.

Figure 1. Cisco Unified Wireless IP Phone 7920 Multi-Charger



Table 1. Features

Feature	Description
Charging Capacity	6 phones and 6 batteries (standard or extended)
Mounting Options	Desk or wall mount
Material	Lead and latex free

Table 2. Specifications

Item	Description
Dimensions (H x W x D)	4.4 x 20.7 x 6.8 in. (112 x 525 x 173 mm)
Weight	<ul style="list-style-type: none">• Multi-charger: 3.4 lb (1.552 kg)• Power supply: 1.4 lb (0.641 kg)• Mounting bracket: 2.2 lb (1.002 kg)• Total weight: 7.0 lb (3.195 kg)
Power Supply	<ul style="list-style-type: none">• Input: 100–240V, 2.2A, 50/60 Hz• Output: 19V, 4A• AC adapters (by geographical region)
Power Consumption	80 watts
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	–22 to 140°F (–30 to 60°C)
Relative Humidity	10 to 95% (noncondensing)
Drop Specification	2.5 ft (0.75m) to concrete
Vibration	1.5 Grms maximum, 0.1" double amplitude @0.887 octaves per minute from 5-500-5 Hz sweep, 10-minute dwell on three major peaks, in each of the three major mutually perpendicular axes
Thermal Shock	–30°C (–22°F) 24 hours; +70°C (158°F) 24 hours
Charging Time	<ul style="list-style-type: none">• Standard battery only: 3 hours• Extended battery only: 4 hours• Phone with standard battery: 4.5 hours• Phone with extended battery: 6 hours

Table 3. Safety and Compliance

Item	Description
Safety	<ul style="list-style-type: none">• UL 60950-1• CSA 22.2 No.60950-1• EN 60950• IEC 60950-1• AS/NZS 60950-1
Electromagnetic Compatibility (EMC) and Electromagnetic Interference (EMI)	<ul style="list-style-type: none">• CFR 47 Part 15 Class A• ICES-003 Class A• EN 55022 Class A• CISPR 22 Class A• VCCI Class A• AS/NZS CISPR22• EN 55024• EN 50082-1• EN 61000-6-1• EN 61000-3-2• EN 61000-3-3

ORDERING INFORMATION

Table 4 gives ordering information for the wireless Cisco Unified Wireless IP Phone 7920 Multi-Charger.

Table 4. Ordering Information

Part Number	Description
CP-MCHGR-7920-BUN	Cisco Unified Wireless IP Phone 7920 Multi-Charger bundle (includes multi-charger, power supply, and AC power cord)
CP-MULTICHGR-7920=	Cisco Unified Wireless IP Phone 7920 Multi-Charger
CP-PWR-MC7920=	Cisco Unified Wireless IP Phone 7920 Multi-Charger power supply
CAB-AC2AUS=	AC power cord for Australia
CAB-AC2E=	AC power cord for Europe
CAB-AC2J=	AC power cord for Japan
CAB-AC2=	AC power cord for North America
CAB-AC2UK=	AC power cord for United Kingdom
CAB-AC2CHI=	AC power cord for China

WARRANTY

The Cisco Unified Wireless IP Phone 7920 Multi-Charger is covered by a Cisco standard one-year replacement warranty. A Cisco SMARTnet® optional service agreement is available.

CISCO UNIFIED COMMUNICATIONS SERVICES AND SUPPORT

Using the Cisco Lifecycle Services approach, Cisco Systems and its partners offer a broad portfolio of end-to-end services to support the Cisco Unified Communications system. These services are based on proven methodologies for deploying, operating, and optimizing IP communications solutions. Upfront planning and design services, for example, can help you meet aggressive deployment schedules and minimize network disruption during implementation. Operate services reduce the risk of communications downtime with expert technical support. Optimize services enhance solution performance for operational excellence. Cisco and its partners offer a system-level service and support approach that can help you create and maintain a resilient, converged network that meets your business needs.



Corporate Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)

