

Cisco SPA 501G Basic 8-Line IP Phone

Q. What is the Cisco SPA 501G?

A. The Cisco® SPA 501G is an 8-line desktop IP phone with paper label, 802.3af Power over Ethernet (PoE), and PC port. It is a full-duplex speakerphone with wideband audio (HD Voice) capability.

Q. When will the Cisco SPA 501G be available to order?

A. The Cisco SPA 501G is available now for order on the wholesale price list (WPL).

Q. What is the part number for ordering the Cisco SPA 501G?

A. The part number is SPA 501G: 8-Line IP Phone with PoE and PC Port.

Q. Who are the target customers for the Cisco SPA 501G?

A. Target customers for the Cisco SPA 501G include the following:

- Home and small offices:
 - Front desk lobby
 - Walkway
- Small businesses with on-premises or hosted private branch exchange (PBX) service that:
 - Want to integrate the SPA 501G with an existing Cisco SPA 9000Voice System, Cisco Unified Communications 500, or hosted voice over IP (VoIP) service with PBX features
 - Need a warehouse telephone
- Industries:
 - Hospitality
 - Food and beverage
 - Legal, medical, or financial services

Q. Who can sell the Cisco SPA 501G?

A. Any authorized partners who can buy the SPA 501G through their distributors.

Q. What accessories are available for the Cisco SPA 501G?

A. An optional power adapter (Cisco PA100 Power Supply for Small Business VoIP) is available for users who choose not to use PoE. A wall-mount kit (Cisco MB100 Wall-Mount Bracket) is available for mounting the phone on a wall, and the Cisco WBP54G Wireless-G Bridge provides a wireless option. The Cisco SPA 500S Expansion Module is available for customers who need an attendant console.

Q. What languages are supported?

A. The following languages will be supported on the phone via a dictionary update: German, French, Dutch, Italian, Spanish, Portuguese, Danish, Norwegian, Swedish, Croatian, Slovenian, Bulgarian, Turkish, Polish, Russian, Hungarian, Czech, and Slovak.

Q. What voice protocols are supported?

A. The Cisco SPA 501G support both Session Initiation Protocol (SIP) version 2 with the Cisco SPA 9000 and third-party call controllers and the Smart Phone Control Protocol (SPCP) with the Cisco Unified Communications 500 Series.

Q. What codecs are supported?

A. The Cisco SPA 501G supports G.711a, G.711u, G.726_32, G.729ab, and G.722 (wideband audio).

Q. Does the Cisco SPA 501G offer a full-duplex speakerphone?

A. Yes, the SPA 501G includes a full-duplex speakerphone with advanced acoustic echo cancellation.

Q. How many independent SIP registrations can the Cisco SPA 501G support?

A. The SPA 501G can support up to four independent SIP registrations.

Q. Does the Cisco SPA 501G support VLAN tagging on the PC port?

A. Yes, the SPA 501G supports the option to configure VLAN tags on traffic originating from the PC port.

Q. What standard calling features are supported?

A. The Cisco SPA 501G supports the following features (some features require support on call controllers):

- Auto answer
- Call waiting, cancel call waiting
- Caller ID with name/number (multinational variants)
- Caller ID blocking
- Call forwarding: no answer, busy, all
- Call transfer
- Call return
- Call back on busy
- Call blocking with toll restriction
- Call park and unpark
- Do not disturb
- Three-way conference calling with local mixing
- Group paging
- Corporate directory access
- Visual message waiting indication
- Distinctive ringing: calling and called number
- Shared call appearance
- Selective/anonymous call rejection

Please refer to the data sheet for complete support features. The Cisco SPA 501G data sheet is available at <http://www.cisco.com/go/500phones>.

Q. Does the Cisco SPA 501G support the full range of Cisco SBCS applications?

A. Yes. The SPA 501G supports the following with UC 500.

- WebEx PhoneConnect
- Time Card View
- Live Record / Live Replay
- Single Number Reach
- VoiceView Express

Q. What types of headsets does the Cisco SPA 501G support?

A. The SPA 501G has a 2.5-mm standard 4-segment phone jack. It supports most universal 2.5-mm wired headsets (non Nokia versions), such as the Jabra C250/C500 (<http://www.jabra.com>) and Plantronics MX250 (<http://www.plantronics.com>).

Q. What types of security can be implemented?

A. The Cisco SPA 501G supports the following security features:

- Certificates/HTTPS
- Secure Real-Time Transport Protocol (SRTP) (media)
- Transport Layer Security (TLS) (signaling), SIP over TLS
- Encrypted configuration files up to 256-bit Advanced Encryption Standard (AES)

Q. Does the Cisco SPA 501G support a Lightweight Directory Access Protocol (LDAP) corporate directory?

A. No, the SPA 501G does not support a corporate directory.

Q. How does a user access the phone menu locally to get phone's IP address?

A. Users can access the phone menu via interactive voice response (IVR). The IVR option for the phone's IP address is 110#.

Q. Does the Cisco SPA 501G support remote management?

A. Yes. Voice configuration parameters can be updated if the service provider uses one of the supported mass provisioning methods (Trivial File Transfer Protocol [TFTP], HTTP, or HTTPS).

Q. Does the Cisco SPA 501G support Extension Mobility with the Cisco Unified Communications 500?

A. No.

Q. Does the Cisco SPA 501G support Extension Mobility with Broadsoft?

A. No.

Q. Is the Cisco Small Business Pro Service available for the Cisco SPA 501G?

A. Yes, customers can purchase a 3-year Cisco Small Business Pro Support Plan.. This plan offers second-day advance replacement and technical support

Q. What type of warranty is provided with the Cisco SPA 501G?

A. The SPA 501G comes with a standard 90-day software warranty and 12-month hardware warranty.

- The 12-month hardware warranty provides 10-business-day advance replacement.
- Customer are eligible for 12 months of S-TAC technical phone support.
- S-TAC technical support provides only basic steps to identify the phone's hardware state for return materials authorization (RMA).

Q. Does the Cisco SPA 501G have a message-waiting indicator LED?

A. Yes.

Q. Does the Cisco SPA 501G work with instant messaging applications?

A. No.

Q. Does the Cisco SPA 501G support syslog?

A. Yes.

Q. What and how many ring tones will the Cisco SPA 501G support?

- A.** The SPA 501G supports 10 built-in and 2 customizable ring tones. The customizable ring tone can be downloaded using the web GUI with the link `http://<phone-ip-addr>/ringtone[1|2][?<url>]`, where <url> syntax is `[[tftp|http|https]:/][host[:port]]/<pathname>`. TFTP, HTTP, and secure HTTP are supported.

Example :

If the phone's IP address is 192.168.2.1, to download the ring tone "music.mid" residing on the HTTP server 192.168.2.100, and store it as "ringtone2," the user would issue the following link on a web browser connected to the same LAN as the phone: <http://192.168.2.1/ringtone2?http://192.168.2.100/music.mid>.

Q. What ring tone formats are supported?

- A.** Table 1 shows the association of ring tone suffix to ring tone format:

Table 1. Ring Tone Formats Supported by the Cisco SPA 501G

Ring Tone Format	Ring Tone Suffix
G.726_32	.726

Q. How can the firmware be upgraded?

- A.** The firmware for the Cisco SPA 501G can be upgraded in any of the following ways:

Remotely: An IP telephony service provider (ITSP) can upgrade the firmware remotely from an HTTP server or by using a profile for the phone.

By downloading .exe firmware and executing it locally on a PC.

The wizard for the Cisco SPA 9000 Voice System ships with the latest firmware for all phones that the SPA 9000 supports, including the SPA 501G. If the SPA 501G will be used with the SPA 900, firmware upgrades can be completed by using the setup wizard.

For details, see the SPA 501G user guide:

http://www.cisco.com/en/US/products/ps10033/products_user_guide_list.html.

Note: In SPCP mode, firmware upgrades for the phones will be initiated by the administrator managing the Cisco Unified Communications 500.

Q. What are the display specifications for the Cisco SPA 501G?

- A.** The SPA 501G does not have a display. It uses a paper label for the line keys.

Q. Can the Cisco SPA 501G support personalized wallpaper?

- A.** No, the SPA 501G does not have a display.

Q. Does the Cisco SPA 501G support embedded Bluetooth?

- A.** No, it does not support integrated Bluetooth. The Cisco SPA 525G supports this feature.

Q. What standards does the Cisco SPA 501G meet?

- A.** The SPA 501G meets the following standards:

- Electromagnetic compatibility (EMC)
 - FCC/CFR 47 part 15 class B
 - ICES-003 class B
 - EN55022 class B
 - AS/NZS 3548 class B

- CISPR 22 class B
- EN 55024
- EN 300.328
- EN 301.489-1
- EN 301.489-17
- Safety
 - UL 60950
 - IEC/EN 60950
 - CSA 22.2 60950
 - ACA TS 001
 - Hearing aid compatibility (HAC)
 - FCC parts 68.316 and 68.317
 - PT220 (New Zealand)

Q. Does the Cisco SPA 501G comply with Restriction of Hazardous Substances (RoHS) standards?

A. Yes.

Q. Where can I learn more about the Cisco SPA 501G?

A. For more information, visit <http://www.cisco.com/go/500phones>.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, CCSI, Cisco Eos, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Lumin, Cisco Nexus, Cisco Nurse Connect, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flip Video, Flip Video (Design), Flipshare (Design), Flip Ultra, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Store, and Flip Gift Card are service marks; and Access Registrar, Aironet, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, EtherFast, EtherSwitch, Event Center, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, iQuick Study, IronPort, the IronPort logo, LightStream, Linksys, MediaTone, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, Network Registrar, PCNow, PIX, PowerPanels, ProConnect, ScriptShare, SenderBase, SMARTnet, Spectrum Expert, StackWise, The Fastest Way to Increase Your Internet Quotient, TransPath, WebEx, and the WebEx logo are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0907R)